

MATERIAL SAFETY DATA SHEET

(COMPLIES WITH 29CFR 1910.1200)

SECTION I - CHEMICAL PRODUCT & COMPANY IDENTIFICATION

Identity (As Used on Label and List): Energize Plus
Product Class: Water-borne floor polish
Emergency Telephone Number: 800-255-3924
Telephone Number for Information: 651-481-1900
Manufacturer's Name and Address:
Multi-Clean®
600 Cardigan Road
Shoreview, MN 55126

SECTION II - COMPOSITION/INFORMATION ON INGREDIENTS

Hazardous Components (Specific Chemical Identity):		
Chemical	Common Name(s)	%
A	Emulsified acrylic polymers (proprietary)	1 - 5
B	Dipropylene glycol methyl ether CAS #34590-94-8	.5 - 1.5
C	Water CAS #7732-18-5	60 - 100
D	Diethylene glycol monoethyl ether CAS #111-90-0	.5 - 1.5

SECTION III - HAZARDS IDENTIFICATION

Emergency Overview
Appearance and Odor: Blue liquid, pleasant fragrance
Primary Hazards: Irritant

Potential Health Hazards
Route(s) of Entry: Skin Absorption: X Ingestion: Inhalation: X
Eye: May cause irritation on contact.
Skin: May cause irritation on prolonged or repeated contact.
Ingestion: May be harmful if swallowed.
Inhalation: No effects expected.
Signs and Symptoms of Exposure: Irritation on direct contact.
Carcinogenicity: NTP? No IARC Monographs? No
OSHA Regulated? No
Target Organ (s): No additional data
Medical Conditions Generally Aggravated by Exposure: N. Av.
Health Hazards, Chronic: N. Av.

SECTION IV - FIRST AID MEASURES

Emergency and First Aid Procedures:
If Swallowed: Do not induce vomiting. Drink water in large amounts and call a physician immediately. Never give anything by mouth to an unconscious person. **Eye Contact:** Flush eyes with running water for at least 15 minutes. If irritation persists, obtain medical attention. **Skin Contact:** Flush thoroughly with cool water. Remove and wash contaminated clothing before reuse.
Sources Used: Raw material data, general toxicology from the trade for similar products.

SECTION V - FIRE FIGHTING MEASURES

Flammability: No **Autoignition Temperature:** N. Av.
Flash Point (method used): None
Flammable Limits: N. Av. LEL UEL
Extinguishing Media: N. Av.
Water? **Foam?** **Water Fog?**
Alcohol Foam? **CO2?** **Dry Chemical?**
Vaporizing Liquid? **Other?**
Special Fire Fighting Procedures: N. Av.
Unusual Fire and Explosion Hazards: N. Av.
TDG Flammability Classification: Non-flammable
Sensitivity to Mechanical Impact: None
Sensitivity to Static Discharge: None

SECTION VI - ACCIDENTAL RELEASE MEASURES

Steps to be Taken in Case Material is Released or Spilled:
Dike and contain spill with inert material (sand, earth, etc). Collect spill with mop, absorbent material (example: floor-dri) or vacuum. Thoroughly rinse affected area with water.

SECTION VII - HANDLING AND STORAGE

Precautions to be Taken in Handling and Storing:
Storage Temperature: Minimum 40°F (4°C); Maximum 100°F (38°C)
Other Precautions: Keep out of reach of children. Keep from freezing.

SECTION VIII - EXPOSURE CONTROLS/PERSONAL PROTECTION

Respiratory Protection (Specify Types): Not required
Ventilation: **Local Exhaust:** Not required **Special:** Not required
Mechanical (General): Normal good ventilation sufficient.
Other: Not required
Protective Gloves: Natural rubber or synthetic.
Eye Protection: Approved safety goggles or glasses. **Footwear:** Not required
Other Protective Clothing or Equipment: Not required
Work/Hygienic Practices: Do not contaminate food or beverages with cleaning chemicals.

SECTION IX - PHYSICAL/CHEMICAL CHARACTERISTICS

Boiling Point: Approximately 212°F **pH:** 8 - 9
Specific Gravity (H2O) = 1: 1.00 **% Volatile:** 60 - 100
Vapor Density (Air = 1): > 1 **Odor Threshold:** N. Av.
Evaporation Rate (Butyl Acetate = 1): N. Av. **Oil/Water Distribution Coefficient:** N. Av.
Solubility in Water: Complete
Vapor Pressure (MM HG): N. Av.
Melting Point: N. Ap.

SECTION X - STABILITY AND REACTIVITY

Stability: **Unstable:** **Stable:** X
Conditions to Avoid: N. Ap.
Incompatibility (materials to avoid): N. Av.
Hazardous Decomposition or By-products: N. Av.
Hazardous Polymerization: **May occur:** **Will not occur:** X
Conditions to Avoid: N. Ap.

SECTION XI - TOXICOLOGICAL INFORMATION

Chemical	OSHA PEL	ACGIH TLV	Recom.	LD50	LC50
A	None	None	N. Av.	N. Av.	N. Av.
B	100 ppm (skin)	100 ppm (skin)	100 ppm (skin)	5.6 g/kg (rat, oral)	> 33,000 ppm (rat)
C	None	None	N. Av.	N. Av.	N. Av.
D	N. Av.	N. Av.	N. Av.	5,000 mg/kg (rat, oral)	> 200 mg/L (1 hr.)

Teratogen, Mutagen, Reproductive Toxin Status: No
Toxicologically Synergistic Products: N. Av.

SECTION XII - ECOLOGICAL INFORMATION

Ecotoxicological Information: N. Av.
Chemical Fate Information: N. Av.

SECTION XIII - DISPOSAL CONSIDERATIONS

Waste Disposal Method:
Solution may contain zinc. Coagulate with ferric chloride or sulfate and then lime. Decant the clear liquid to a sewer. Dispose of the coagulum by sanitary landfill or incinerator. Follow all existing pollution control ordinances.
RCRA Hazard Class: None

SECTION XIV - TRANSPORT INFORMATION

Shipping Classification: Buffing or polishing compound
UN Number: N. Av.
Packing Group: N. Av.

SECTION XV - PREPARATION DATA

Prepared By: Mike Elms
Telephone Number: 651-481-1900
Date: 12-09

SECTION XVI - REGULATORY INFORMATION

US Federal Regulations
TSCA Status: All ingredients listed.
CERCLA Reportable Quality: None
SARA Title III
Section 302 Extremely Hazardous Chemicals: None
Section 311/312 Hazard Category: Immediate health hazard
Section 313 Toxic Chemicals: Diethylene glycol monoethyl ether (glycol ether).
State Regulations
International Regulations
WHMIS Controlled Product Hazard Class: D2B

SECTION XVII - OTHER INFORMATION

None
N. Ap. - Not Applicable; N. Av. - Not Available

NFPA SYSTEM

1 A. Health Hazard 0 A. Fire Hazard 0 A. Reactivity Hazard

THE INFORMATION CONTAINED HEREIN IS BASED ON DATA CONSIDERED ACCURATE, HOWEVER NO WARRANTY IS EXPRESSED OR IMPLIED REGARDING THE ACCURACY OF THESE DATA OR THE RESULTS TO BE OBTAINED FROM THE USE THEREOF. MINUTEMAN INTERNATIONAL, INC. ASSUMES NO RESPONSIBILITY FOR PERSONAL INJURY OR PROPERTY DAMAGE TO VENDEES, USERS OR THIRD PARTIES CAUSED BY THE MATERIAL. SUCH VENDEES OR USERS ASSUME ALL RISKS ASSOCIATED WITH THE USE OF THE MATERIAL.