

# Decorative HD-3000

## Waterborne Industrial Concrete Coating



### For an enhanced appearance on Concrete floors

Designed to add a "terrazzo" look to your concrete, Decorative HD-3000 is a proven water-borne two-part epoxy that offers comparable durability and chemical resistance to solvent-based coatings. Multi-colored decorative chips are scattered into the wet coating to create an attractive, decorative appearance.

Decorative HD-3000 is a specially packaged kit containing the base color HD-3000 with multi-colored decorative chips that are immediately broadcast into the coat after application. Detailed instructions are included with each kit. Each do-it-yourself kit of Decorative HD-3000 covers approximately 600 sq. ft. (56 sq. meters). A floor coated with Decorative HD-3000 brightens a facility and greatly enhances lighting efficiency.

Great for use in: Locker Rooms \* Restrooms \* Garages \* Kitchens \* Laboratories \* Utility Rooms \* Lobbies \* Basements \* Employee Break Rooms \* Display Areas \* Correctional Facilities \* Butcher Shops \* Delis



- Tough 2 part Epoxy
- Low odor
- Chemical Resistant
- VOC Compliant
- Attractive high gloss
- Improved wet slip resistance

Decorative HD-3000 meets or exceeds Federal and State VOC (Volatile Organic Compounds) regulations.

### Properties

#### Abrasion Resistance:

Tabor abrasion .....	25 mg loss (CS-17 wheel, 1000 gram load)
Dry Time .....	12 - 16 hours (before recoat)
Slip Resistance .....	Exceeds 0.5 min. static of friction (James Machine)
% Solids A & B .....	45 ± .5%
Coverage .....	350 - 450 sq. ft./gal. (32-42 sq. meter/gal.)
VOC (minus water) .....	less than 150 grams/liter
Application Floor Temp ....	60°F (15°C) minimum
Pot Life (maximum) .....	3 hours at 70°F (21°C)
Induction Time .....	15 minutes

#### Chemical Resistance:

Caustic Soda (50%) .....	Resistant
Isopropyl Alcohol .....	Resistant
Mineral Spirits .....	Resistant
Butyl (2-butoxy ethanol) ..	Resistant
10% Hydrochloric Acid .....	Resistant

FOR INDOOR USE ONLY.

Learn More.....at [www.multi-clean.com](http://www.multi-clean.com)

\*Training materials: Multi-Clean Method Bulletin | 1425 provides detailed concrete floor care procedures. \*Calculators: Easy online calculator provides estimates of product usage for a project.



WARNING & DISCLAIMER: Results may vary. Multi-Clean chemicals are to be used only by appropriately trained personnel. IMPROPER USE POSES RISK OF PHYSICAL INJURY OR PROPERTY DAMAGE. See appropriate Multi-Clean Method Bulletin for further warnings and information for your application. The suitability of and proper application of this product is the responsibility of the applier. The manufacturer disclaims all warranties, express and implied, including any warranties of MERCHANTABILITY AND FITNESS OF PURPOSE. The manufacturer's liability is limited to replacement of or reimbursement for any product proved defective. No person has authority to waive these disclaimers or make any representations or warranties on behalf of the manufacturer, except in writing signed by the manufacturer.

### Packaging

1.4 gallon, 909153

# Multi-Clean®

600 Cardigan Road, Shoreview, Minnesota 55126 Phone 651-481-1900 Fax 651-481-9987 Web [www.multi-clean.com](http://www.multi-clean.com)

1-25-07

1535D