

Acryl-Kote[®]

Seal and Finish



Modified Acrylic Tile, Terrazzo and Concrete Seal

ACRYL-KOTE SEAL AND FINISH is essentially an odorless, water-based product formulated with top quality metal cross-linked polymers and light colored resins which provide a tough, clear seal and finish that is remarkably resistant to discoloration.

ACRYL-KOTE provides a tough, satin-like finish that brings out the natural color and beauty of floors and prevents dusting of terrazzo, oxychloride and concrete floors. Its penetrating action seals out dirt, water and stain-causing materials and helps prevent chipping, dusting and pitting. It preserves the beauty of new asphalt, vinyl, vinyl composition, and linoleum floors and revives and brings out the natural beauty of even worn, porous floors. It is also recommended to be used on synthetic sports floors and concrete. It's odor-free, and an excellent product for use in hospitals, hotels and food processing plants. Authorized by USDA for use in federally inspected meat and poultry plants.

ACRYL-KOTE SEAL AND FINISH may be applied with a short string mop or wax applicator. Average coverage is 1,500 to 2,000 sq. ft. per gallon on tile floors. Average drying time - 30 to 45 minutes. Two coats are recommended on all floors where it is used alone as the seal and finish. Where used as a seal, with additional coats of a Multi-Clean resinous finish, only one coat of ACRYL-KOTE is needed. No etching needed on concrete floors, normally just a thorough cleaning.



Acryl-Kote exceeds slip resistance when tested according to ASTM D-2047. (James Machine)

Properties

Appearance	Low viscosity, milky white emulsion
Color Retention	Excellent
pH	9.2 ± 0.1
Flashpoint	None
Specific Gravity	1.026- 1.030
Non-Volatile (solids content)	17%
Slip Resistance	Passes ASTM D2047, average coefficient of friction 0.5 minimum
Coverage	1,500 - 2,000 sq. ft. per gallon on tile floor and terrazzo
Drying Time	30 - 45 min. (normally)
Dry Hard	2 hours
Removability	Removable with Multi-Clean strippers
Minimum Application Temp	50°F
Storage Temperature	40°F minimum, 100°F maximum
Storage Stability	Excellent, 1 year under normal conditions
Freeze-Thaw Stability	Passes three cycles

Packaging

55 gallon, 903377
5 gallon, 903375
1 gallon, 903373

Learn More.....at www.multi-clean.com

- *Training materials: Multi-Clean Method Bulletin 1415 provides detailed floor care procedures.
- *Calculators: Easy online calculator provides estimates of product usage for a project.



WARNING & DISCLAIMER: Results may vary. Multi-Clean chemicals are to be used only by appropriately trained personnel. IMPROPER USE POSES RISK OF PHYSICAL INJURY OR PROPERTY DAMAGE. See appropriate Multi-Clean Method Bulletin for further warnings and information for your application. The suitability of and proper application of this product is the responsibility of the applicator. The manufacturer disclaims all warranties, express and implied, including any warranties of MERCHANTABILITY AND FITNESS OF PURPOSE. The manufacturer's liability is limited to replacement of or reimbursement for any product proved defective. No person has authority to waive these disclaimers or make any representations or warranties on behalf of the manufacturer, except in writing signed by the manufacturer.

Multi-Clean[®]