

# RSB

## Finish Maintainer



### Versatile

A multiple use finish restorer formulated for high and ultra high speed floor care systems. R.S.B. can be used with all Multi-Clean floor finishes.

### Easy to Use

R.S.B. can be used as a mop-on restorer, as a high speed spray burnishing compound, or as a cleaner restorer through an automatic scrubber.

### Labor Saver

Quick and easy to apply, R.S.B. restores the "wet look" on floors while providing excellent scuff, scratch and black heel mark resistance.

An Ultra High Speed Maintenance Program utilizing PRIME SHINE and R.S.B. will greatly prolong the periods between costly stripping operations thus reducing your overall labor costs.



**RSB exceeds slip resistance when tested according to ASTM D-2047. (James Machine)**

### Properties


Appearance .....	Light blue emulsion
pH .....	9.2 - 9.3
Flashpoint .....	None
Specific Gravity .....	1.021 - 1.025
Non-Volatile (solids content) .....	17 - 18% by wt.
Hardness .....	Soft
Slip Resistance .....	Passes ASTM D2047
Dilution: Spray burnish .....	1:8 (16 oz. per gallon)
Mop on .....	1:3 (45 oz. per gallon)
Repairability .....	Excellent
Spray Burnishing .....	Excellent
Leveling Ability .....	Excellent
Drying Time .....	Approx. 20 minutes
Minimum Application Temperature .....	50°F
Storage Temperature .....	40°F minimum, 100°F max
Storage Stability .....	Excellent, 1 year normal conditions
Freeze-Thaw Stability .....	Passes three cycles

### Packaging

55 gallon, 904927  
5 gallon, 904925  
1 gallon, 904923

**Learn More.....at [www.multi-clean.com](http://www.multi-clean.com)**

- \*Training materials: Multi-Clean Method Bulletin 1415 provides detailed floor care procedures.
- \*Calculators: Easy online calculator provides estimates of product usage for a project.



WARNING & DISCLAIMER: Results may vary. Multi-Clean chemicals are to be used only by appropriately trained personnel. IMPROPER USE POSES RISK OF PHYSICAL INJURY OR PROPERTY DAMAGE. See appropriate Multi-Clean Method Bulletin for further warnings and information for your application. The suitability of and proper application of this product is the responsibility of the applicator. The manufacturer disclaims all warranties, express and implied, including any warranties of MERCHANTABILITY AND FITNESS OF PURPOSE. The manufacturer's liability is limited to replacement of or reimbursement for any product proved defective. No person has authority to waive these disclaimers or make any representations or warranties on behalf of the manufacturer, except in writing signed by the manufacturer.

