

Clear Essence

Certified Floor Finish



Clear Essence is based on a polymer cross-linking technology that does not require the use of zinc or other heavy metals to produce a durable, high quality finish with excellent long term removability.

Clear Essence combines the benefits of conventional zinc metal interlock finishes without the environmental drawbacks. (Zinc has been found to interfere with waste water treatment processes.) In addition, Clear Essence does not give off harsh ammonia fumes during application making the product ideal for use in hospitals, nursing homes, schools and other areas where odor must be kept to a minimum. Clear Essence exhibits excellent burnish response using high speed and ultra high speed equipment.

Clear Essence can be used as both a seal and a finish to achieve a high gloss appearance with excellent scuff, mark, soil, and detergent resistance. StainLess, a zinc free sealer, can also be used as a part of a complete zinc free system.

The Clear Essence *Certified Floor Care System*:

- Clear Essence - Seal/Finish
- Ultra Stripper - Floor Stripper
- Century Maintenance - Daily Cleaner



This product meets the Green Seal™ environmental standard for industrial and institutional cleaners based on its reduced human and environmental toxicity and reduced volatile organic compound contents.

Learn More.....at www.multi-clean.com

- *Training materials: Multi-Clean Method Bulletin 1415 provides detailed floor care procedures.
- *Calculators: Easy online calculator provides estimates of product usage for a project.



WARNING & DISCLAIMER: Results may vary. Multi-Clean chemicals are to be used only by appropriately trained personnel. IMPROPER USE POSES RISK OF PHYSICAL INJURY OR PROPERTY DAMAGE. See appropriate Multi-Clean Method Bulletin for further warnings and information for your application. The suitability of and proper application of this product is the responsibility of the applicator. The manufacturer disclaims all warranties, express and implied, including any warranties of MERCHANTABILITY AND FITNESS OF PURPOSE. The manufacturer's liability is limited to replacement of or reimbursement for any product proved defective. No person has authority to waive these disclaimers or make any representations or warranties on behalf of the manufacturer, except in writing signed by the manufacturer.



Clear Essence exceeds slip resistance standards when tested according to ASTM D-2047.

Properties

Appearance	Milky white liquid
Non-Volatile (solids)	19.5 - 20.5
Coverage	1500 - 2500 sq. ft./gallon
Drying Time	30 - 40 minutes
Application Temp	50° F (minimum)
Storage Stability	Excellent, 1 year normal conditions
Freeze-Thaw Stability	Passes three cycles

FOR INDOOR USE ONLY.

Packaging

5 gallon, 904105

Multi-Clean®