

# DECADE<sup>®</sup> 100

## 25% Solids Floor Finish



### Ultra Gloss Finish

DECADE 100<sup>®</sup> is a 25% high solids finish that provides maximum gloss and protection per coat. The product contains more non-volatile solids than conventional products which means fewer coats are needed saving you time and labor costs. DECADE 100 goes down smooth and easy, recoats beautifully and dries quickly.

DECADE 100 is so flexible it can be used in programs based on high speed, ultra high speed or low speed. It holds up beautifully under high intense traffic and intense maintenance including nightly burnishing.

DECADE 100 keeps coming back with a sparkling shine that stands up to the heaviest traffic. Optical brighteners in DECADE 100 help make spectacular looking floors by enhancing light reflectivity and shine.

### SoilShield<sup>™</sup> Technology

Dirt is the natural enemy of high gloss-high traffic floors causing discoloration and a dingy appearance over time. Soil Shield<sup>™</sup> is exclusive Multi-Clean technology that makes DECADE 100 dramatically more dirt resistant than conventional finishes. Soil Shield<sup>™</sup> means floors clean-up better and look brighter for longer periods.

### The DECADE 100 Challenge

Compare the durable performance of DECADE 100 side by side with other finishes and you will see the difference:

- *Less scuffing/marking*
- *Holds shine longer*
- *Requires less recoating*
- *Exceptional dirt resistance*
- *Optical brighteners enhance gloss*

The bottom line is floors look better and last longer without stripping, saving you time and money.

Learn More.....at [www.multi-clean.com](http://www.multi-clean.com)

\*Training materials: Multi-Clean Method Bulletin 1415 provides detailed floor care procedures.

\*Calculators: Easy online calculator provides estimates of product usage for a project.



WARNING & DISCLAIMER: Results may vary. Multi-Clean chemicals are to be used only by appropriately trained personnel. IMPROPER USE POSES RISK OF PHYSICAL INJURY OR PROPERTY DAMAGE. See appropriate Multi-Clean Method Bulletin for further warnings and information for your application. The suitability of and proper application of this product is the responsibility of the applicator. The manufacturer disclaims all warranties, express and implied, including any warranties of MERCHANTABILITY AND FITNESS OF PURPOSE. The manufacturer's liability is limited to replacement of or reimbursement for any product proved defective. No person has authority to waive these disclaimers or make any representations or warranties on behalf of the manufacturer, except in writing signed by the manufacturer.



DECADE 100 exceeds slip resistance standards when tested according to ASTM D-2047 (James Machine).

### Properties

Appearance .....	Milky white liquid
Finish Type .....	Extended wear
Non-Volatile (solids) .....	25 ± .5%
pH .....	9.0 - 9.3
Weight/Gallon .....	8.61 - 8.68
Slip Resistance .....	Exceeds .5 static coefficient
Coverage .....	2000 - 3000 sq. ft./gallon
Soil Resistance .....	Excellent
Drying Time .....	35 - 45 minutes
Color of Dry Film .....	Water clear
Application Temperature ...	50°F (minimum)
Storage Temperature .....	40°F minimum, 100°F maximum
Storage Stability .....	1 year under normal conditions
Freeze-Thaw Stability .....	Passes three cycles

### Packaging

55 gallon, 904497  
5 gallon, 904495  
1 gallon, 904493

# Multi-Clean<sup>®</sup>

600 Cardigan Road, Shoreview, Minnesota 55126 Phone 651-481-1900 Fax 651-481-9987 Web [www.multi-clean.com](http://www.multi-clean.com)

12-04-06

1587