

Performax Finish Floor Finish



Multi-Clean PERFORMAX is a durable high gloss finish designed for maximum economy that can be used in all types of maintenance programs. PERFORMAX responds well to all types of burnishing equipment and low speed spray buffing. PERFORMAX provides excellent performance in an economical finish.

PERFORMAX can be used as a seal and finish or be used in conjunction with a sealer. PERFORMAX can be used with PREP FLOOR SEAL, ACRYL-KOTE, or STAINLESS seal.

Available in 17% or 20% solids.



Performax 20 exceeds slip resistance when tested according to ASTM D-2047. (James Machine)

Properties

Appearance	Milky white liquid
pH	8.6 ± .2
Specific Gravity	1.02 - 1.04
Flashpoint	None
Non-Volatile Content	20%
Slip Resistance	Exceeds .5 static coefficient
Classification	Semi-buffable
Coverage	2500 sq. ft./gallon
Drying Time	30 - 40 minutes
Minimum Application Temp. .	50°F
Storage Temperature	40°F min., 100°F max.
Freeze-Thaw Stability	Passes three cycles
Storage Stability	Excellent, 1 year

Learn More.....at www.multi-clean.com

- *Training materials: Multi-Clean Method Bulletin 1415 provides detailed floor care procedures.
- *Calculators: Easy online calculator provides estimates of product usage for a project.



WARNING & DISCLAIMER: Results may vary. Multi-Clean chemicals are to be used only by appropriately trained personnel. IMPROPER USE POSES RISK OF PHYSICAL INJURY OR PROPERTY DAMAGE. See appropriate Multi-Clean Method Bulletin for further warnings and information for your application. The suitability of and proper application of this product is the responsibility of the applicator. The manufacturer disclaims all warranties, express and implied, including any warranties of MERCHANTABILITY AND FITNESS OF PURPOSE. The manufacturer's liability is limited to replacement of or reimbursement for any product proved defective. No person has authority to waive these disclaimers or make any representations or warranties on behalf of the manufacturer, except in writing signed by the manufacturer.

Packaging

- 55 Gallon (17%) 950737
- 5 Gallon (17%) 950735
- 1 Gallon (17%) 950733
- 55 Gallon (20%) 950767
- 5 Gallon (20%) 950765
- 1 Gallon (20%) 950763

Multi-Clean®