MULTI-Stat Finish quickly dissipates harmful static charges.

DIRECTIONS: 1. Strip old finishes, 2. Rinse floor after stirpping, allow to dry. 3. Optional: On porous tile floors, 2 coats of StainLess can be used as a base coat seal. 4. apply MULTI-STAT FINISH evenly with a clean, rayon-cotton finish mop. Expected coverage is 2,000-2,500 sq. ft./gallon. 5. Allow to dry 2 hours before appying second coat. 6. Apply up to 4 coats (2 or more hours between coats). Maintenance: *The floors can be deep scrubbed and recoated periodically with MULTI-STAT Finish: use an automatic scrubber, blue pad and TAKE CHARGE II at 8 oz./gallon. Follow up with a water rinse. Up to 2 coats may be applied.

For Emergency Medical Information Call toll-free: 1-800-255-3924



600 Cardigan Road Shoreview, MN 55126 Phone 651-481-1900 www.multi-clean.com

Multi-Stat Floor Finish

Ready-To-Use Dilution Pret A Utilise Dilución Lista Para Usarse



CAUTION/ATTENTION/PRECAUTION

See product label and SDS for additional information Voir l'étiquette du produit et de la SDS pour plus d'informations Warning

Causes mild skin irritation. Causes eye irritation. May cause damage to central nervous system, liver, and/or kidneys through prolonged or repeated exposure.Do not breathe dust, fume, gas, mist,

vapors, spray. Wash hands thoroughly after handling. If skin irritation occurs: Get medical attention. IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If eye irritation persists: Get medical attention. Get medical attention if you feel unwell. Dispose of contents in accordance with local regulations.

HMIS rating for diluted product. Classement HMIS pour produit dilué. Health 1 Santé 0 Flammable 0 Reactivity 0

Réactivité

4=Severe Hazard Danger sévier 3=Serious Hazard Danger sérieux 2=Moderate Hazard Danger modéré 1=Slight Hazard Risque faible 0=Minimal Hazard Risque minime