Poli-Mirro[™] 450

Premium Oil-Modified Urethane Finish



Proven Performance

POLI-MIRRO 450 offers the exceptional performance of premium oil modified urethane finishes. POLI-MIRRO 450 offers the superior gloss and durability users of POLI-MIRRO 450 have come to know and expect. Ideal for gym floors, POLI-MIRRO 450 resists black marking and scuffing from athletic shoes. The higher solids content of POLI-MIRRO 450 means a thicker wear layer is applied with each coat.

Seal and Finish in One

POLI-MIRRO 450 can be used as a seal on new or freshly sanded wood floors as well as a finish.

Goes Down Easy

POLI-MIRRO 450 is easily applied using a number of different methods. The Padco Floor Coater, Lambswool Applicator and Tank Applicators are all acceptable methods for applying this product.

FOR INDOOR USE ONLY.

Multi-Clean recommends the following enamel paint for lining when using Hi-Polamur.

Benjamin Moore Impervo

Follow specific lining instructions in the Wood Floor Method Bulletin 1420.

Learn More.....at www.multi-clean.com

*Training materials: Multi-Clean Method Bulletin 1420 provides detailed floor care procedures.

*Calculators: Easy online calculator provides estimates of product usage for a project.



WARNING & DISCLAIMER: Results may vary. Multi-Clean chemicals are to be used only by appropriately trained personnel. IMPROPER USE POSES RISK OF PHYSICAL INJURY OR PROPERTY DAMAGE. See appropriate Multi-Clean Method Bulletin for further warnings and information for your application. The suitability of and proper application of this product is the responsibility of the applier. The manufacturer disclaims all warranties, express and implied, including any warranties of MERCHANTABILITY AND FITNESS OF PURPOSE. The manufacturer's liability is limited to replacement of or reimbursement for any product proved defective. No person has authority to waive these disclaimers or make any representations or warranties on behalf of the manufacturer, except in writing signed by the manufacturer.



600 Cardigan Road Shoreview, Minnesota 55126 Phone 651-481-1900 Web www.multi-clean.com



Use Hi-Trac Wood Floor Cleaner to keep floors clean and maintain a high traction surface.

Properties

Appearance	Amber liquid
Odor	Solvent odor
Flashpoint	104F
% Solids	52.5%
Slip Resistance	Exceeds 0.5%
Coverage	400-600 sq. ft./gal. (recoat)
Dry Time	4-6 hours
	17-24 hours for recoat
Storage	1 year under normal conditions
Freeze Thaw	Does not freeze
VOC (minus water)	Less than 450 grams/liter

Packaging

5 gallon, 903345