

Multi-Clean®
Your Guide to Clean

Splendor®

*Your Best
Utility Player!*



- Dries Fast and is Easy to Apply
- Use in Any Maintenance Program
- Excellent Gloss and Durability
- Your Best Value in a Finish



**Versatile Floor Finish
with BMR Technology**



Splendor®

Versatile Performance Floor Finish



Exceptional Durability: Floors Look Better . . . Longer

Find out what loyal users have known for years; SPLENDOR keeps it shine longer, resists scuffs and black marks, all with less maintenance resulting in savings of time and money.

Brilliant Gloss . . . Exceptional Clarity

SPLendor produces a high shine with clarity that produces sharp, distinct mirror images. This high shine and clarity produces a more brilliant gloss that enhances a floor's appearance. Use on all types of resilient tile as well as terrazzo type floors.

Lasting Beauty

SPLendor produces a water clear film, which is especially important for today's light colored floors. With proper maintenance, stripping and recoat cycles can be further extended.

Easy to Use . . . Easy to Apply . . . Spectacular Results

SPLendor goes down smooth and easy with no mop drag and levels perfectly. The product dries fast and recoats easily for trouble-free performance time after time.

Versatile Performance

SPLendor can be used in high speed maintenance programs using battery, electric or propane machines. It also works well with low speed spray buffing using Buff N Clean.

Designed with black mark resistant technology!



Learn More.....at www.multi-clean.com

*Training materials: Multi-Clean Method Bulletin 1415 provides detailed floor care procedures.

*Calculators: Easy online calculator provides estimates of product usage for a project.



WARNING & DISCLAIMER: Results may vary. Multi-Clean chemicals are to be used only by appropriately trained personnel. IMPROPER USE POSES RISK OF PHYSICAL INJURY OR PROPERTY DAMAGE. See appropriate Multi-Clean Method Bulletin for further warnings and information for your application. The suitability of and proper application of this product is the responsibility of the applicator. The manufacturer disclaims all warranties, express and implied, including any warranties of MERCHANTABILITY AND FITNESS OF PURPOSE. The manufacturer's liability is limited to replacement of or reimbursement for any product proved defective. No person has authority to waive these disclaimers or make any representations or warranties on behalf of the manufacturer, except in writing signed by the manufacturer.

Multi-Clean®

600 Cardigan Road
Shoreview, Minnesota
Phone 651-481-1900
Web www.multi-clean.com



Splendor exceeds slip resistance standards when tested according to ASTM D-2047 (James Machine).

Properties

Appearance	Milky white liquid
Drying Time	15 - 30 minutes
Color of Dry Film	Water clear
Non-Volatile (solids)	19 ± .5%
pH	9.0 - 9.3
Weight/Gallon	8.55 - 8.65
Slip Resistance	Exceeds .5 static coefficient of friction
Coverage	2000 - 4000 sq./ft./gallon
Finish Type	Versatile
Application Temperature	50° F (minimum)
Storage Temperature	40° F minimum, 100° F maximum
Storage Stability	1 year under normal conditions
Freeze-Thaw Stability	Passes three cycles
VOC Compliant - VOC Free	



Packaging

55 gallon drum, 904887
2 x 2.5 gallon case, 904885