



Multi-Clean[®]
Your Guide to Clean

Multi-Matte

Low Gloss Finish



- Low Gloss
- Low Odor
- Low Maintenance



Multi-Matte

Low Gloss, Low Odor Floor Seal/Finish



Low Gloss - Low Odor

Multi-Matte Finish offers the performance of a highly cross-linked, durable floor finish with a matte finish. Use on floors where a high gloss shine is not desired. Use Multi-Matte Finish in hospitals, nursing homes, schools, supermarkets and other retail stores.

Hi-Performance, Low Maintenance

Multi-Matte Finish is used in facilities with high traffic areas or are open 24 hours a day, 7 days a week. The fast drying formula produces a tough, low maintenance floor. Exceptional durability can translate into less frequent recoats and stripping, saving time and labor.

For best results, floors should be completely stripped of existing finish before applying 2 coats of Multi-Matte. The level of shine can be increased slightly, if desired, by applying a 3rd coat.

Matte Finish

The low gloss appearance makes this finish perfect for use in health care facilities, especially in areas that deal with dementia and/or alzheimer patients.

Low Odor

This finish creates the optimum combination of high performance polymers with additives that do not produce the unpleasant odors associated during traditional application of floor finish. Use in health care facilities that may have patients and staff who are sensitive to traditional floor finish odors.

Floor Types

Use on VCT, Luxury vinyl tile, rubber, true linoleum, laminate, and concrete.



Multi-Matte exceeds slip resistance standards when tested according to ASTM D-2047 (James Machine).

Properties

Appearance	Milky white liquid
Finish Type	Extended wear
Non-Volatile (solids).....	15 ± .5%
pH	8.5 - 9.0
Specific Gravity.....	1.03
Slip Resistance	Exceeds .5 static coefficient of friction
Coverage	2000 - 3000 sq. ft./gallon
Soil Resistance	Excellent
Drying Time	35 - 45 minutes
Color of Dry Film.....	Crystal clear.....Matte Gloss
Application Temperature.....	50F (minimum)
Storage Temperature.....	40F minimum, 100F maximum
Storage Stability	1 year under normal conditions
Freeze-Thaw Stability.....	Passes three cycles
VOC (minus water).....	2.0% (21g/L)
VOC Compliance - EPA, IL, IN, MI, OH, OTC, UT, and Canada regulations	

Learn More.....at www.multi-clean.com

- *Training materials: Multi-Clean Method Bulletin 1415 provides detailed floor care procedures.
- *Calculators: Easy online calculator provides estimates of product usage for a project.



WARNING & DISCLAIMER: Results may vary. Multi-Clean chemicals are to be used only by appropriately trained personnel. IMPROPER USE POSES RISK OF PHYSICAL INJURY OR PROPERTY DAMAGE. See appropriate Multi-Clean Method Bulletin for further warnings and information for your application. The suitability of and proper application of this product is the responsibility of the applicator. The manufacturer disclaims all warranties, express and implied, including any warranties of MERCHANTABILITY AND FITNESS OF PURPOSE. The manufacturer's liability is limited to replacement of or reimbursement for any product proved defective. No person has authority to waive these disclaimers or make any representations or warranties on behalf of the manufacturer, except in writing signed by the manufacturer.



600 Cardigan Road
Shoreview, Minnesota
Phone 651-481-1900
Web www.multi-clean.com



Designed with black mark resistant technology!

Packaging

1 gallon, 904653