



Defoamer

Foam Doesn't Stand A Chance

Concentrated Defoaming Agent

- Use in Extractor or Scrubber Tanks
- Knocks down foam quickly
- Silicone Based





Defoamer

Silicone-Based Defoamer/Anti-Foam



DEFOAMER is a silicone-based defoamer formulated to effectively control foam generated during carpet extraction cleaning.

DEFOAMER should be applied directly to the recovery systems of carpet extraction equipment, wet vac's or autoscrubbing machines.

DO NOT ADD DEFOAMER TO SOLUTION TANK OR DIRECTLY TO CARPET.

DIRECTIONS:

SHAKE WELL BEFORE USE.

- 1. For best results to control foam, add 2-3 ounces of DEFOAMER to 1-2 gts. of warm water (15-25 ml/ liter) and mix.
- 2. Remove hose from wand and vacuum DEFOAMER solution into recovery tank.
- Reconnect hose to wand.
- 4. Or add 2 oz. and 1/2 gallon (15 ml/litre) of water to vacuum recovery tank and mix slightly.
- 5. If carpet has been shampooed often, additional DEFOAMER may be required to control foam.

Learn More.....at www.multi-clean.com

Training materials: Multi-Clean Method Bulletin 1401, "Carpet Care" provides detailed carpet care procedures.





DEFOAMER should be applied directly to the recovery systems of carpet extraction equipment, wet vac's or autoscrubbing machines.

Properties	
Appearance	Milky white, slightly viscous
	liquid, mild odor.
pH	6 - 8
Specific Gravity	
Flashpoint	
Dilution	Use 2 ounces in 1/2 gal/warm
	water per recovery tank
Phosphate Free	Yes
Storage Stability	
	•

Freeze-Thaw Stability...... Will freeze - usable after thawingwith no change in performance. Agitate after

thawing and before use.

VOC Compliant - VOC Free

Packaging

1 gallon, 910543

Learn More Online...







600 Cardigan Road Shoreview Minnesota Phone 651-481-1900 www.multi-clean.com