

ECO-SHEEN

High Performance Floor Finish

Description

Eco-Sheen high performance floor finish provides maximum gloss and protection per coat. The product contains more non-volatile solids than conventional products which means fewer coats are needed saving you time and labor costs.

This product keeps the sparkling shine that stands up to the heaviest traffic. Optical brighteners help make spectacular looking floors by enhancing light reflectivity.

Eco-Sheen Technology

Dirt is the natural enemy of high gloss-high traffic floors causing discoloration and a dingy appearance over time.

Eco-Sheen's technology make it more resistant to dirt and black marks than conventional finishes. This technology means better clean-up and brighter looking floors.

Compatible With:

High speed, Ultra High Speed and Low Speed Programs.

Use On:

VCT, Sheet Vinyl, LVT, Linoleum, or Terrazzo Flooring.

The Eco-Sheen Challenge

Compare the durable performance of Eco-Sheen side by side with other finishes.

- Less scuffing/marking
- Holds shine longer
- Requires less recoating
- Exceptional dirt resistance
- Optical brighteners enhance gloss



Eco-Sheen exceeds slip resistance standards

Properties

Appearance.....	Milky white liquid
Finish Type.....	Extended wear
pH.....	9.0 - 9.3
Weight/Gallon.....	8.61 - 8.68
Slip Resistance.....	Exceeds .5 static coefficient
Coverage.....	2000 - 3000 sq. ft./gallon
Soil Resistance.....	Excellent
Drying Time.....	35 - 45 minutes
Color of Dry Film.....	Water clear
Application Temperature.....	50°F (minimum)
Storage Temperature.....	40°F minimum, 100°F maximum
Storage Stability.....	1 year under normal conditions
Freeze-Thaw Stability.....	Passes three cycles
VOC (minus water).....	0
VOC Compliant - VOC Compliant	



Packaging	
Size	Part no.
BIB 5 Gallon	904065

